MONITOR
OBSTRUCTION

PANEL A

PANEL B

Formulate:

10′ Designer Series 07



Panel A
Total graphic area: 67.4375″w X 99.625″h
Total visual area: 63.4375″w X 95.625″h

Panel B
Total graphic area: 85.9375″w X 99.625″h
Total visual area: 81.9375″w X 95.625″h

Please be sure to include the 2″ bleed around the perimeter to compensate for finishing of the graphics. Do NOT design any critical elements (text, logos, etc.) within 2″ of the edge (see innermost gray area).

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 100-120 ppi
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

bleed area
trim line
safe area

MONITOR
OBSTRUCTION

PANEL A

Formulate:
10’ Designer Series 07

Panel A
Total graphic area: 67.4375”w X 99.6
Total visual area: 63.4375”w X 95.62

Panel B
Total graphic area: 85.9375”w X 99.6
Total visual area: 81.9375”w X 95.62

Please be sure to include the 2” bleed around the perimeter to compensate finishing of the graphics. Do NOT des any critical elements (text, logos, etc.) within 2” of the edge (see innermost gray area).

General Art Guidelines

- CMYK Color Mode
- All Solid Coated Pantone colors sho be called out in the art as spot color
- Embed all images and support files
- Resolution must be 100-120 ppi
- All fonts must be created to outline
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from templa in your artwork as they will not prin

Formulate:
10’ Designer Series 07



Panel A
Total graphic area: 67.4375”w X 99.625”h
Total visual area: 63.4375”w X 95.625”h

Panel B
Total graphic area: 85.9375”w X 99.625”h
Total visual area: 81.9375”w X 95.625”h

Please be sure to include the 2” bleed around the perimeter to compensate for finishing of the graphics. Do NOT design any critical elements (text, logos, etc.) within 2” of the edge (see innermost gray area).

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 100-120 ppi
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

PANEL B

bleed area
trim line
safe area