#### Canis 20' x 20' Truss System Dye Sub Printed

#### **TEMPLATE IS @ 1/2 SCALE**

Panels CA1-A, CA1-B, CA1-C, CA1-D: Total Graphic Area: 42.125"w x 87.75"h Finished Size: 38.125"w x 83.75"h

Panels CA2-A, CA2-B, CA2-C, CA2-D: Total Graphic Area: 47"w x 87.75"h Finished Size: 43"w x 83.75"h

Panels CA3-A, CA3-B, CA3-C, CA3-D: Total Graphic Area: 78.75"w x 41.75"h Finished Size: 74.75"w x 37.75"h

Panels CA4-A, CA4-B, CA4-C, CA4-D: Total Graphic Area: 42.125"w x 87.75"h Finished Size: 38.125"w x 83.75"h

Panels CA5-A, CA5-B, CA5-C, CA5-D: Total Graphic Area: 47"w x 87.75"h Finished Size: 43"w x 83.75"h

Template requires 1" bleed around the perimeter (2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4"w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

#### **General Art Guidelines:**

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

-bleed area

- trim line

#### BS OR-G-CA3-A

## BS OR-G-CA3-B

#### BS OR-G-CA3-C

#### BS OR-G-CA3-D

gray area will be obstructed once finished and mounted

# FS OR-G-CA1-A

bleed area trim line

# FS OR-G-CA2-A

# FS OR-G-CA4-A

#### FS OR-G-CA5-A

# FS OR-G-CA1-B

# FS OR-G-CA2-B

# FS OR-G-CA4-B

#### FS OR-G-CA5-B

# FS OR-G-CA1-C

bleed area
trim line

# FS OR-G-CA2-C

# FS OR-G-CA4-C

#### FS OR-G-CA5-C

# FS OR-G-CA1-D

# FS OR-G-CA2-D

### FS OR-G-CA4-D

#### FS OR-G-CA5-D